

SELF-ADHERING FRICTION REDUCING LINER AND METHOD OF USE

BACKGROUND OF THE INVENTION

insert ar

5 The present invention relates to the use of
very low friction material formed into patches or pieces
and adhered to the skin or to a surface in contact with
the skin (or immediately adjacent material such as a
sock) to lower the magnitude of tangential traction of
the surface in contact with the skin. The material
10 reduces the likelihood of abrasion, trauma and
ulceration in localized areas.

In the prior art, there have been efforts to
reduce the co-efficient of friction of materials in load
bearing contact with the skin, such as the surface of a
15 lining of a shoe, which slides against a stocking. Also
the regions where a limb prosthesis is in load bearing
contact with a residual limb have been extensively
considered for ways of reducing problems. The co-
efficient of friction of smooth leather varies,
20 depending on the moisture content, and when it gets wet
can be quite high in friction. Moleskin patches have
been sold and used for covering corns on the feet, as
well as covering calluses, but this also has a
relatively high co-efficient of friction against the
25 inner surface of a shoe and the co-efficient of
friction increases substantially when the moleskin is
wet.

Blisters, abrasions, calluses, bursas and even
some forms of sub-cutaneous tissue trauma are the result
30 of applications of a combination of forceful contact and
tangential tractions to the skin (forceful
rubbing/forceful shearing). High shear stresses may

cause damage in a single cycle. Low shear stresses may cause tissue damage when the number of cycles is great.

Tangential skin tractions relate directly to tissue shear stress and shear strain magnitudes. Shear strain is by its very nature very distortional and, when it exceeds certain levels, results in the tearing of biological tissues such as blood capillaries and interface (skin-subcutaneous) layers. High normal pressures (perpendicular to the skin surface) in the absence of significant tangential tractions are surprisingly well tolerated by skin and underlying tissue, especially when applications are of a short enough duration to avoid ischemic trauma (cell death after an extended period of blood flow blockage).

*15
insert 92*
~~This invention is primarily aimed at reducing and preventing shear trauma from many repetitions of short duration skin loadings, but eliminating shear tractions even in low repetition, long-duration loadings is of value. Research shows that even capillary blood flow is affected strongly by whether or not shear stresses are superimposed on normal pressures. When high shear stresses are present, capillary blood flow has been shown to be occluded at normal pressures only half as great as what are required to occlude flow in the absence of shear stresses and strains.~~

There is some recognition among medical researchers and care-givers that shear plays a role in tissue trauma. However, how and when excessive shear stresses/strains occur and how they damage tissue are hard to visualize. Injury from a normal force (a simple, yet forceful, blow or bump causing injury by crushing tissue) is easier for people to visualize and understand. Shear stresses and how they vary over a given area (and vary with time) are very hard to

measure; much harder than it is to measure normal pressure. In addition to the visualization and measurement difficulties just mentioned, there is the fact that few people have better than a vague
5 qualitative awareness of how something called the "coefficient of friction" (C.F.) relates to blisters, abrasions, and calluses. Tangential traction force magnitudes can be no greater than the C.F. times the magnitude of normal force. Therefore, the simplest,
10 most direct way to reduce shear induced tissue trauma is to choose materials which minimize friction against the at-risk skin surface areas. Until the present invention, there has been little practical awareness of, and attention given to, friction management.

15 Examination and knowledge of products on the market indicate that the opportunities for reducing callusing, blistering and abrasions by friction management has been almost entirely unappreciated by designers of shoes, orthoses, prostheses, and many other
20 objects that come in repeated or prolonged contact with the human body.

Thin silk or synthetic fiber sheets have been used by amputees to pull over their residual limbs before pulling on a cotton or wool sock and then donning
25 the limb prosthesis. The co-efficient of friction between the sheet and the sock is reduced under dry conditions and does protect the residual limb to some extent from friction and consequent shear-related trauma. The coefficient of friction increases
30 substantially when the material becomes damp or wet. In most cases, the material used to line shoes and prosthesis sockets, for example, represent high friction choices. Foam products are used to line prosthetic sockets, orthoses, and shoe insoles and represent a

particularly poor material from the standpoint of friction management. Damp skin and sock material literally sticks to such foams.

5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155
10160
10165
10170
10175
10180
10185
10190
10195
10200
10205
10210
10215
10220
10225
10230
10235
10240
10245
10250
10255
10260
10265
10270
10275
10280
10285
10290
10295
10300
10305
10310
10315
10320
10325
10330
10335
10340
10345

purpose of the low friction material is to lower the magnitude of tangential tractions that the surface of the object can exert against the skin.

The use of intervening layers is contemplated in the present invention, so a sock or sheet placed between the low friction pad and the skin does not adversely affect the performance.

A low friction surface layer used may be on material in the form of a sheet, or a small patch that is pre-cut, or custom cut to a desired size, and having a pressure sensitive adhesive on the surface of the patch opposite from the low friction surface. The adhesive may be on the outer surface of another layer of material, such as a foam backing cushion layer or a stretch fabric backing bonded to the low friction material. A release paper is placed on the exposed adhesive. When the release paper is removed, the patch or piece of material providing the low friction surface layer can be adhered into a certain desired position of the surface of the skin or on the object that bears on the skin.

mount *ay* *made*
Preferably, the low friction layer is a thin film material ~~having the surface friction characteristics~~ of polytetrafluoroethylene (PTFE) The PTFE layer is preferably bonded to a fabric layer of a somewhat elastic, flexible material such as Lycra or a Lycra blend. The exposed side of the fabric is covered with a pressure adhesive and a release paper is on top of the adhesive.

The thin sheet of PTFE material can be used without any backing sheets by applying adhesive directly to the PTFE layer. Bonding a very thin sheet of PTFE to a stretch fabric without having the PTFE separate from the fabric during use gives the desired low friction

characteristics of the outer surface, while permitting the formed patch to conform to irregular shapes or surfaces, because of the stretch fabric underneath the thin layer of PTFE. The stretch fabric also gives the
5 thin layer of low friction material, such as PTFE, "body" so it can be handled reasonably during the release paper stripping and application of the layer or patch to the desired surface. Very thin layers of PTFE
10 tend to wrinkle or fold and cause problems with getting them very smooth. The elasticity of the backing fabric allows conformance into recesses, over convexities, and onto a combination of compound contoured surfaces.

Cushioning material, such as foam can be placed between the patch and the surface supporting the patch,
15 if desired, to provide a cushioning effect, as is known. Various shapes can be made, including shapes which would have the stretch fabric toward the center of the patch or piece so that it was surrounded by an adhesive coated thin low friction material.

20 A preferred method of use includes placement of suitable size pieces or patches of the low friction coefficient material either on the skin or on the surface that will be next to the skin in locations where shear trauma is likely to occur. These patches or
25 pieces can be held in place with suitable adhesive on the back side of the low friction material. Foam or other compressible material for cushioning can be used wherever needed.

Another aspect or form of the protective patch
30 is the PTFE film or layer bonded to a calf skin leather hide, textile foam liner, or other material that could be used to line the inner wall of the toe box of a shoe. The composite material can be sewn and applied in the same manner as the lining material now is applied

without a PTFE film surface. The usefulness of this material is realized in its ability to shield dorsal and peripheral surfaces of the foot from damaging shear forces. At these non-plantar locations, high tangential
5 tractions can be present, but more often trauma develops from lower forces, that generate excessive callus/corn growth and/or tissue breakdown by the action of cyclic (high frequency) loading.

The patches of the present invention offers an
10 easy way to accomplish "friction management". The surfaces that a shoe, orthosis, or prosthesis present to the skin vary as to their function and as to the tissue trauma risk they present. It is also true that some areas of the anatomy within a shoe, prosthesis, or
15 orthoses are at greater or lesser risk because of the level of peak forces and/or the amount of soft tissue interposed between skin and bone. Some parts of an orthosis bear only slightly or not at all against the corresponding skin surface. Other parts bear very
20 firmly in order to provide maximum orthopedic support, correction, or weight bearing. Still other surfaces such as the supra-condylar parts of a BK (lower leg) prosthesis socket serve to suspend (during swing-through) or maintain position of the device.

25 All of these just-noted facts are important because they are reasons to vary the friction coefficient depending on the surface function. For instance, there is very little reason to be concerned about the friction coefficient of a surface in only very
30 light contact with the skin (unless the number of repetitions is very high). Forceful cyclical contact against a skin surface is a situation that benefits more from minimizing the friction coefficient. If the area is "bony" minimizing friction becomes more important.

In a case like the supra-condylar suspension areas of the BK socket mentioned earlier, high friction (even "sticky") materials may be desired. Applying the low friction patches of an aspect of the invention to certain areas and not others is a way to add friction management to the orthotist's (prosthetist's, podiatrist's, etc.) treatment methods and appliances. In cases where the professional wishes to apply maximum supportive/corrective pressure the near elimination of friction and shear in selected regions means that much greater support can be safely provided without approaching tissue trauma conditions.

There are also many consumer (non-professional) applications for the present invention. Many people are plagued by excessive callus build-up. A person with excessive calluses under the metatarsal heads might remove the shoe insoles and apply low friction patches to the corresponding surface of the insole. If the excessive callus is in the form of "corns", the person could apply a low friction corn pad to relieve some pressure on a painful corn (by means of annular cushioning material) and greatly reduce the friction and shear which originally generated, and then maintains the corn callus.

A similar but much larger patch might be applied by a skater over ankle bones to allow tight(er) lacing with greater comfort and less chance of trauma at the apices of those bony prominences. As an alternative, the skater may choose to adhere the patch to the appropriate locations on the inside surface of the skate uppers. There are a myriad of other possibilities such as on kneeling pads (for cement workers, etc.) or on backpack shoulder straps.

A similar (but non-consumer) use of the cushioned patch (continuous, annular, or donut types) is in hospitals for prevention of bed sores. Low friction cushion patches of the present invention applied over healthy bony areas such as sacrum-coccyx, greater trochanter, heels, and elbows as a prophylactic measure act to inhibit the generation of bed sores.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a plan view of a layer of material made with a low friction surface material according to the present invention;

Figure 2 is a sectional view taken on line 2--2 in Figure 1 showing the layers used;

Figure 3 is a plan view of a form of patch;

Figure 4 is a sectional view of a patch made according to an aspect of the present invention, taken on line 4--4 in Figure 3 including a layer of low friction material that will lower friction loads on the skin in a selected area;

Figure 5 is a cross sectional view of a modified aspect of the present invention;

Figure 6 is a plan view of a further modified patch made according to the present invention;

Figure 7 is a sectional view taken on line 7--7 in Figure 6;

Figure 8 is a plan view of a further modified patch made according to the present invention;

Figure 9 is a sectional view of the patch shown in Figure 8 taken on line 9--9 in Figure 8;

Figure 10 is a schematic representation of a typical shoe showing regions having patches made according to the present invention installed for reducing shear damage to tissue;

Figure 11 is a perspective view of an ankle and foot orthosis showing locations where patches having a low friction surface according to the present invention are installed, and which can be installed either on the orthosis as shown, or as shown in Figure 12 on a foot on which the orthosis will be worn;

Figure 12 is a schematic showing of a foot and ankle indicating desired locations of low friction patches for an orthosis;

Figure 13 is a top plan view of a prosthetic socket for a lower leg prosthesis showing regions on the interior of the socket where low friction pads would be installed to reduce tissue trauma caused by shear;

Figure 14 is a schematic representation of a leg and knee that would fit into the prosthesis of Figure 13, and showing locations of low friction patches made according to the present invention;

Figure 15 is a perspective view of a longer leg prosthetic device having a socket for receiving the upper portion of a leg to which the prosthesis would be attached and illustrates locations of low friction patches made according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figures 1 and 2 illustrate a simple form of the invention which includes a composite sheet 10 made in a suitable size, which can be used for cutting individual interface patches or pieces from the sheet. The composite sheet 10 includes a thin film or layer 12 of polytetrafluoroethylene (PTFE). Layer 12 is preferably bonded to a stretch fabric layer 14, such as Lycra or stretch nylon, which also is relatively thin. The top layer of PTFE can be in the range of 2.5 mils thick, and the layer of fabric 14 could be slightly thicker than that, as needed to make a suitable stretch

weave. The PTFE film 12 is conformable and will stretch, so that the stretch fabric will cause the PTFE layer to move with it, if it is stretched in any direction. A thin layer of adhesive 16 is shown in the drawings on an opposite side or surface of fabric layer 14 from the PTFE layer 12. A suitable release paper 18 is provided over the adhesive on the fabric.

The sheet 10 can be used for cutting out various configuration, such as those shown in dotted lines at 20, for custom fitting patches of the low friction material 12. It can be seen that the low friction material film 12 has an upper surface 13 which faces, and supports, the skin. Also as shown schematically perforations 15 can be provided for breathability of the patch. When the patch such as that shown by dotted lines 20 is placed on the skin, for an interface with a shoe, prosthesis, or orthosis, as desired the surface 13 faces away from the skin. The purpose of applying the patch is to lower the magnitude of tangential traction that the surface of an object worn by a person can exert against the skin. The PTFE film is bonded to one surface of the fabric layer, and is available from Chemfab Corporation of Merrimack, New Hampshire, USA.

The sheet 10 is usable in large areas, or can be cut for small areas as desired. Premanufactured special size and shape patches or pieces can be made, as shown in Figure 3 where a patch 26 is illustrated in generally a rectangular configuration. An exploded section of the patch 26 is shown in Figure 4, except that in Figure 3 the release paper is shown removed to provide a view of a foam layer 30 around which the adhesive layer 32 extends. The sectional views are

shown exploded, for illustration but the layers are bonded together in use.

5 The patch 26 comprises a film or layer 28 of the low friction material, such as PTFE, bonded to a plastic foam layer 30 that is of smaller size than the PTFE film layer. The foam 30 is shown in Figure 4 to be substantially thicker than the PTFE film layer, but it can be any thickness desired. The pressure sensitive adhesive layer 32 is then applied, and can be provided
10 only on the peripheral edges as shown in Figure 3, to provide an open center where the foam layer 30 would be exposed for contact with the skin. A release paper layer 34 overlies the bottom of the patch. The exterior surface 29 of the PTFE film layer 28 provides the low
15 friction surface for reducing shear and tangential traction against a support surface or material. The foam layer 30 may be in contact with the skin or the surface of the support to provide cushioning and protection. The foam layer 30 could be, for example, in
20 the range of a quarter inch thick, but would have tapered or skived edges as shown so that the PTFE film layer 28 would conform well to the foam. The adhesive used is selected to bond to the PTFE layer so there is an adhesive edge for adhering the patch on the skin or
25 other surface. The adhesive is a pressure sensitive adhesive.

The preformed patch 26 shown in Figure 3 can be sized to be 2, 3, or 4 inches long, for example, with widths of 1, 1/2 and 2 inches. The patch 26 thus can be
30 used for any application where a spot or region of skin is subject to shear and abrasion, so the tissue is becoming tender, to relieve the tangential traction on that portion of the skin.

Figure 5 illustrates an exploded cross section of a modified patch 36 having the periphery shown in Figure 3. The patch 36 has a PTFE film layer 38. The PTFE film layer 38 is bonded to a stretch fabric layer 40 such as stretch nylon or Lycra. A foam layer 42 is bonded to the fabric layer 40 in the center portions of the patch. The pressure sensitive adhesive layer 44 is placed on the surface of the fabric layer opposite from the low friction outer surface 39 of PTFE film layer 38. The adhesive layer 44 again can be formed as shown in Figure 3 with a rim of adhesive surrounding an open center where the foam layer 42 is exposed. A release paper 46 is also provided on the patch as shown in cross section. As stated, the PTFE films can be perforated as desired.

The use of the stretch fabric 40 provides an additional layer of cushioning and protection, which can be stretched along with the PTFE film to fit rounded surfaces or irregularities. The foam layer 42 has its edges beveled, and the stretch fabric layer 40 and the PTFE film layer 38 will fit closely around the foam. The stretch fabric layer 40 is bonded to the PTFE film layer 38 before placing the foam in position, so both the fabric and the PTFE would be stretched at the same time. This bonding, again, is done commercially by Chemfab Corporation of Merrimack, New Hampshire, USA. The PTFE film also can be bonded to leather and other fabrics by ChemFab Corporation.

Peripheral dimensions of the patches for the construction shown in Figure 5 can be the same as those shown in connection with Figure 3, and the bottom view would be the same as well. Of course other configurations such as elliptical shapes and the like can be used. The pressure sensitive adhesive layer 44

can extend all the way across the foam, so there is no open center, if desired.

In Figures 6 and 7 a modified form of the invention is shown, which has low coefficient of friction film on both surfaces of the patch, so when the patch that is shown in Figure 7 is placed on a corn or callus, the surface in contact with the skin has the low coefficient of friction and the outwardly facing surface does also. The patch 50, as shown is elliptically shaped, and in Figure 7 a cross sectional exploded view is illustrated. A PTFE film layer having a low coefficient of friction outer surface 53 is bonded to a stretch fabric layer 54 and then a foam layer 56 that has a hole 57 through the center is provided in the center portions of the patch 50. In this form of the invention, a layer 60 of PTFE film that is relatively small in size is positioned in the hole 57 in the foam and is bonded to the fabric layer for example with pressure sensitive adhesive. A pressure sensitive adhesive layer 58 is then bonded to the stretch fabric layer 54 and the underside of the foam layer 56 but surrounding the hole 57. A release paper layer 59 overlies the bottom surface of patch 50 and over the adhesive. The layer of PTFE film 60 is shown in both Figures 6 and 7, and has an outwardly facing low coefficient of friction surface 61 that will reduce any abrasion of skin that it contacts.

The foam layer 56 has a generally elliptically shaped periphery as shown in dotted lines in Figure 6, and the overall configuration then would be a patch 50 that could be adhered to skin, to provide a low friction material directly against the skin with the small layer of film 60, and a larger area of low friction film

defined by layer 52 that could engage the lining of a shoe or the inner surface of a sock or the like.

Figures 8 and 9 illustrate a further modified form of the invention comprising an elliptically shaped piece or patch 66 that is made of a layer 68 of PTFE film having an outer low coefficient of friction surface 69. Layer 68 is bonded to a stretch fabric layer 70. A second layer of PTFE film 72, is smaller in size than the top PTFE film layer 68 and the stretch fabric 70 and is bonded to the stretch fabric 70 in the center portions of the patch on an opposite side of the fabric from the PTFE film layer 68. This can be seen in Figure 8.

A layer of pressure sensitive adhesive 74 is then applied to the peripheral rim area surrounding the film layer 72, and will provide for an adhesive layer of sufficient size to permit adhering the patch 70 to the skin, or objects or supports for the skin. A release paper layer 75 is provided. This patch is made without any cushioning or foam layer. The smaller center layer 72 of PTFE film does not have any adhesive between it and the skin, so this is not adhered to the skin, but has a low friction surface 73 that is free to slide against the skin. This reduces the friction on the load carrying surfaces significantly, and reduces trauma from shear, even when it is of low magnitude. Low magnitude shear can cause tissue damage if it cycles repeatedly.

Figure 10 illustrates schematically a foot within a shoe drawn in phantom to illustrate in cross section, regions where high load and/or rubbing areas can benefit from the application of the low friction patches made according to the present invention. In Figure 10, the bones of the foot are illustrated at 80, and they are shown within the outline of a shoe 82.

High load bearing areas of course are located under the metatarsal heads 84, the heel or calcaneus 90, and the end of the toes, in particular the big toe 97. The metatarsal heads 84 are supported on a patch 86. This patch 86 can be on top of the insole 87 and thus between the sock (and foot) and the support provided by shoe 82. The patch 86 can be installed in the shoe 82 permanently, by sewing if desired. Patch 86 provides a low friction surface area where the sock can slide easily relative to the surface of the patch 86 and will not tend to abrade against the skin of the foot in the high load support area.

The patch or pad 86 can extend across the width of the metatarsals, so that the entire metatarsal head region (the metatarsal-phalangeal joint region) of the foot is supported on a relatively low friction surface. The patch or pad 86 preferably has an outer PTFE film layer, backed by a stretch fabric and held in place on the shoe insole. A foam layer as shown in Figure 5 can be provided in the patch or pad 86, if desired.

Another region that can be supported is at the toe end surfaces, in particular the big toe, such as that shown with a pad 88 under end of the big toe 97. This is a region that is not subjected to extremely high loads, but there is a lot of cyclic loading, including shearing, as one moves. The toe supports forces as the person pushes off on each stride, particularly when running.

The heel bone or calcaneus indicated at 90 has a bony prominence 92, that is supported on a patch 94 having a low coefficient of friction outer surface region. The patch or pad 94 will provide support and reduce any shear loads if there is slippage during the

stride. Additionally, the cushioning patches that are shown, having a foam layer can provide some cushioning support and conformability around protrusions in the heel bone to reduce trauma and damage.

5 A non-load-bearing area where cyclic shear loads can cause damage is shown above a toe where a joint may be deformed or contracted so the bone is raised up as shown at 96 and will tend to rub against an upper surface of the toe box 98 of the shoe 82. The
10 installation of a pad 100 directly on the toe, or on the interior of the shoe on the top interior surface of the toe box will reduce the shear loading to a point where even cyclical loading will not cause shear damage, blistering, callusing or the like. In a nonweight-
15 bearing area, therefore, the low friction surface patches also provide relief. Bonding PTFE film to leather permits lining the toe box of a shoe to reduce friction in the entire toe region.

 The patches or pads of the present invention
20 find needed application in ankle-foot orthoses. One such orthosis is shown in Figure 11, at 104 and includes a foot support shell 106, and ankle and leg support shell 108 joined together with flexure members 110 in a conventional manner so that the foot shell 106 can be
25 flexed relative to the leg support. The shells are open in the front and top, as can be seen, and a retaining strap 112 is used for retaining the leg in position. Additional securing devices can be used for the foot.

 The interior surfaces of the shells 106 and
30 108 support the foot, the ankle, and the lower leg snugly, but there can be some sliding or shear forces generated. A patch 114 that is relatively large and which can be cut from the form of the invention shown in Figure 1, is positioned in the longitudinal arch area.

Suitable foams can be used between the shell surface and the pad, a low friction material PTFE is provided on the top surface of the patch that engages the underside of a foot in the orthosis, through a sock, in this high
5 load support area. The pad or patch 114 can be configured to provide support in the arch area as well as reducing the friction loads that occur from any sliding, particularly under high forces. The patch 114 can be made as shown before with foam underneath the
10 PTFE film layer. Use of a stretch fabric layer backing the PTFE film is desired because of some irregular contours that have to be followed on the formed foot shell 106.

The low friction surface pads used where there
15 is flexing, insures that the shear loads are very low, and have the advantage of having foam attached or bonded to the film surface. Conventional foam pads are very high friction and will tend to cause tissue damage from repeated shear loads even though direct weight support
20 is not present. Additionally, a medial leg support patch or pad shown at 120 can be provided above the ankle bone, and this includes foam padding behind a PTFE film layer for increasing or modifying the pressure distribution and provide increased corrective forces.
25 The pad 120 can be again cut to the desired shape, and suitable foams can be used under the PTFE layer. Here, too, the pad preferably has the bonded stretch fabric beneath the outer PTFE film layer because of the need of conforming to irregular contours.

30 The edges of the shell can be lined with the low friction surface patches or pads 122 to reduce shear in these regions. The patches or pads can be folded over the edges and adhered in place. The main portion of

the pads on the edges should be on the interior surfaces.

Figure 12 illustrates a typical foot and lower ankle joint, and the region shown at 114A, where the pad or patch 114 would bear on the arch. The upper pad or patch region on the leg is shown at 120A.

Figure 13 is a top view of a typical transtibial prosthetic leg 123. The prosthetic leg 123 includes a rigid socket 124 and a soft socket liner 125 which will receive a residual limb, and support the residual leg at and just below the knee. In such a prosthesis, there are regions where tissue is thin over bony prominences, such as at the lateral, anterior and bony prominences near the top of the tibia and the tibia crest. These regions are also shown in Figure 13, and pads shown at 126 and 128 for bony prominences are placed appropriately in the socket liner 125. The socket has a rigid shell 124 that normally has a liner 125 made of a suitable material such as a foam or gel. The patches according to the present invention provide for low friction support between a covering sock or layer of material and the supporting surface. In Figure 14, the tibial crests, the medial and lateral bony prominences near the top of the tibia are indicated at 130A, 126A, and 128A. The patches or pads can have foam underneath the low friction film layer. The low friction surfaces reduce shear loading against the skin and subcutaneous tissue when the skeleton moves relative to the socket. The outer shell 124 supports a lower leg portion of the prosthesis.

Additionally, the tibial crest pad 130 of Figure 13 is aligned with the tibial crest shown at 130A in Figure 14. The pad 130 has the PTFE film outer layer bonded to a stretch fabric because of irregular contours

that have to be followed on the socket. Suitable foam padding can be provided to insure some load distribution and conformability onto the tibial crest.

Another bony area of support for a lower leg prosthesis is the fibular head shown at 132A in Figure 14. A fibular head pad 132 (Figure 13) is placed to cushion the lateral side of the remaining limb and around the rear of the leg. The head of the fibula bone is quite close to the skin surface in these locations, so that very high pressure and shear loads are carried in this region and damage can easily occur. The patches of the present invention reduce the friction between the limb and the supporting surfaces of the socket, to provide for a smooth surface that is very low friction so that the tissue is not subjected to shear loading. The upper edges of the socket 124 can be lined with patches, if desired.

Figure 15 is a view of a socket used for a full leg prosthesis (trans-femoral amputation), where support is provided at the femur and pelvic bones. The shell shown at 140 has an upper socket region 142, and the lower portion 143 that supports a knee joint, pylon 144 and a foot prosthesis 146.

In this instance, a large patch or pad 150 made according to the present invention can be provided in the frontal area where loads will be directly applied to relatively soft tissue, and this will reduce frictional loads as soft tissue tends to move, for example, the residual limb tends to move in and out as the upper leg flexes between sitting and standing positions. the reduction in frictional loads is achieved by having the PTFE film layer on the exterior and the patch or pad adhered to the socket so that it

does not slide on the socket. Friction loads on the remaining limb portion is greatly reduced.

Also the patch or pad 152 avoids shear as weight is applied to the socket, which causes relative shifting of the limb and shell.

Additionally, an irregularly shaped patch or pad 152 is provided along a rear rim or edge portion of the socket, where relatively high loads are encountered. This pad or patch 152 can be provided with the stretch fabric layer bonded to PTFE film for conformability. A foam layer can underlie the stretch fabric. The layer of PTFE on the exterior reduces friction in the high load contact area between the socket support regions and the remaining limb and pelvic bones. Other regions can also be covered with the pads of the present invention to provide a low friction interface between the remaining limb and the socket. Foam layers can be used where needed.

A series of tests were conducted between the available products on the market for corn pads, liners, and the like, used in shoes and other regions where support relative to the skin is desired, as well as other materials, such as adhesive bandages. The following Tables 1, 2 and 3 show average coefficient of friction values and standard deviations for dry and wet interface tests. Nine trials were performed for each test in measuring coefficient of friction, and the results averaged.

In the tests a sled surface was covered with the sock material and moved across the test material while the force measurements were made.

S.S. 6-12-98 ^{incline angle}
JMC 6/15/98

TABLE 1

| 5 | SURFACE MATERIAL | DRY TEST | | WET TEST | |
|----|---|----------|-------------------|----------|-------------------|
| | | Ave | St Dev | Ave | St Dev |
| | SOFT MATERIALS | | | | |
| | BockLite 1/8" | 0.49 | 0.10 | 0.56 | 0.03 |
| | Orthopedic Cowhide | 0.49 | 0.11 | 0.68 | 0.03 |
| 10 | PPT with Ultrilure® Top Coverup | 0.57 | 0.07 | 0.57 | 0.02 |
| | IPOCON® Gel with Lycra Top Coverup | 0.41 | 0.08 | 0.48 | 0.02 |
| | Moleskin J&J | 0.63 | 0.03 | 0.87 | 0.03 |
| | PE Lite 1/16" | 0.51 | 0.08 | 0.48 | 0.02 |
| 15 | Plastazote .125" | .57 | 0.06 | 0.51 | 0.05 |
| | Diab-A-Sheet - PPT side up, plastazote down | 0.55 | 0.09 | 0.67 | 0.03 |
| | Russett Cow Leather | 0.41 | 0.15 | 0.62 | 0.06 |
| 20 | PRESENT INVENTION | | | | |
| | Pad of Figure 4 | 0.16 | 0.02 2 | 0.16 | 0.02 |
| | Pad of Figure 2 | 0.16 | 0.02 2 | 0.17 | 0.02 2 |

25

6-12-98 S.S.
JMC 6/15/98

TABLE 2

| | SURFACE MATERIAL | DRY TEST | | WET TEST | |
|----|--------------------------------------|----------|-------------------|----------|-------------------|
| | | Ave | St Dev | Ave | St Dev |
| 5 | BANDAGES | | | | |
| | Band-Aid® Clear From J & J | 0.47 | 0.01 | 0.53 | 0.01 |
| | Band-Aid® Large From J & J | 0.46 | 0.04 | 0.53 | 0.03 |
| 10 | Band-Aid® Plastic From J & J | 0.45 | 0.02 | 0.51 | 0.03 |
| | Blister-Care From Curad® | 0.78 | 0.01 | 0.76 | 0.07 |
| 15 | Clean Seals From 3M | 0.64 | 0.02 | 0.57 | 0.02 |
| | Duoderm CGF From Convatec | 0.38 | 0.03 | 0.30 | 0.01 |
| | Nexcare Active Strips™ From 3M | 1.01 | 0.02 | 0.61 | 0.01 |
| 20 | Sheer Bandages From Walgreens | 0.59 | 0.04 | 0.58 | 0.04 |
| | PRESENT INVENTION | | | | |
| 25 | Pad of Figure 4 | 0.16 | 0.01 2 | 0.16 | 0.02 |
| | Pad of Figure 2 | 0.16 | 0.01 2 | 0.17 | 0.01 2 |

6-12-98 S.S.
JMC 6/15/98

TABLE 3

| 5 | SURFACE MATERIAL | DRY TEST | | WET TEST | |
|----|-----------------------|----------|-------------------|----------|-------------------|
| | | Ave | St Dev | Ave | St Dev |
| | PLASTICS | | | | |
| | Orthoplast | 0.29 | 0.02 | 0.46 | 0.09 |
| | Modified Polyethylene | 0.28 | 0.03 | 0.30 | 0.03 |
| | CO Polyester | 0.27 | 0.04 | 0.41 | 0.01 |
| 10 | Polypropylene | 0.23 | 0.02 | 0.34 | 0.05 |
| | PRESENT INVENTION | | | | |
| | Pad of Figure 4 | 0.16 | 0.06 2 | 0.16 | 0.02 |
| 15 | Pad of Figure 2 | 0.16 | 0.04 2 | 0.17 | 0.04 2 |

6-12-98 s.s.
JMC 6/15/98

20 In Table 1 above, Bocklite is a product manufactured by Otto Bock Othopedic, Inc. Of Minneapolis, Minnesota; Orthopedic Cowhide and Russett Cowhide leather are available from Roden Leather of Royal Oaks Michigan; Diab-A-Sheet, a composite sheet of Plastazote and PPT foam layers and PPT with Ultrilure® top cover are both available from The Langer Biomechanics Group Inc of Deer Park, New York; IPOCON® gel with Lycra top cover is sold by IPOS Orthopedics Industry, Niagara Falls New York; Moleskin is an adhesive bandage sold by J.N. Johnson Sales of Minneapolis, Minnesota; PE Lite and Plastazote (a polyethylene film) are sold by Pel Supply Company of Cleveland, Ohio.

30 In Table 2, all Band-Aid® products and Orthoplast are made by Johnson & Johnson Consumer Product, Inc. of Skillman, New Jersey; Clean Seals and Nexcare™ Active Strips™ are from 3M Health Care of St. Paul, Minnesota; Blister-Care is distributed by A Beiersdorf Co. of Milford, Ohio; Duoderm CGF is

35

distributed by the ConvaTec Division of E.R. Squibb & Sons, Inc. of Montreal, Quebec, Canada; Sheer bandages are from Walgreens Co. of Deerfield, Illinois.

5 In Table 3, modified Polyethylene and Co-Polyester are distributed by American Plastics of Ft. Worth, Texas; and the Polypropylene is from Seelye Plastics, Inc. of Bloomington, Minnesota.

10 It can be seen that the pads of the present invention maintain lower friction characteristics whether the cotton socks used were wet or dry. For testing the "wet" socks were saturated with steam at 150°F. Some of the material such as BockLite did not vary substantially between wet and dry conditions (high friction in both cases), but other commonly used natural
15 liners such as orthopedic cowhide, moleskin, russett leather, and the like increased in coefficient of friction substantially in the presence of moisture. The presence of moisture is common where perspiration will cause socks to become damp.

20 Studies in relation to the causation of ulcers on the skin indicate that when there is a relatively high level of shear, the pressure necessary to produce blood flow occlusion is reduced substantially from when little shear is present. This means that providing low
25 friction surface patches in critical areas, where shear forces can be generated will tend to reduce the likelihood of formations of ulcers or calluses.

30 In bony areas, such as the lower leg area, shear displacements from pistoning motions result in higher shear strains where the tissue is thinnest, the shear strain is a function of the tissue thickness to the bony support. Thus, at the front edge of the leg, a similar shear displacement of the outer skin results in a higher shear strain than at the rear or fleshy part

of the leg. Shear strain is a function of the shear displacement divided by the thickness of tissue between the surface of the skin and the bony support.

Thus, the present invention relates to the use
5 of a very low friction film under both dry and moist conditions, having a support surface that substantially reduces the coefficient of friction that is active to cause shear loads on skin supported on that particular film, whether through a sock, a cloth material of some
10 kind, or directly against the skin. In so doing, the likelihood of ulceration, calluses, or similar problems caused by shear strains and stresses is reduced. The size and shape of the pads can be custom made as desired, the pads can be used with or without foam
15 cushioning. The pressure sensitive adhesive used is a convenient way of applying pads in regions where temporary relief may be made, but the film can be also permanently stitched into the interfaces of a shoe or boot, or of a prosthetic device, such as a prosthetic
20 limb. Installation of pads in orthoses is also very convenient. Treatment can be carried out for spots that seem to be developing sores or which become tender, by placing a low friction patch between the load bearing area of the body or skin and the object that is applying
25 the load so that shear is reduced in that localized area. Thus, the method of treatment includes adding suitable sized patches in regions between tender or sole areas of the skin and the shoe or support object.

Although the present invention has been
30 described with reference to preferred embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.